

Quality Products. Service Excellence.

Fan Panel Assembly PPG Series

Features



- Choice of two or three fan models mounted on a standard width 19" rack panel shipped assembled as shown.
- The front of the panel is punched for finger protection and the rear of the fans assembled with metal guards
- Perfect as an exhaust fan panel or when using "push-pull" cooling (ie..unit pulls air out of the rack cabinet)
- Rugged textured black powder paint finish.
- Two (2) or Three (3) fan daisy chain wire lead/cord, 72" in length.
- TAA-compliant for GSA Schedule purchases.
- · RoHS Compliant.
- Manufactured in North America.

LIANT







Gallery











Accessories

Mounting Hardware

| | Number | Voltage | Fan | | | Mounting Dimensions | |
|------------|---------|------------|-----------|------------|-------------|---------------------|--------|
| Part No. | of Fans | (50/60Hz.) | Panel CFM | Noise (dB) | 115VAC Plug | Rack Units | Height |
| PPGPFPA | 2 | 115 VAC | 210 | 60 | Yes | 3U | 5.25 |
| PPGPFPA230 | 2 | 230 VAC | 210 | 60 | No | 3U | 5.25 |
| FP3F115 | 3 | 115 VAC | 315 | 63 | Yes | 3U | 5.25 |
| FP3F230 | 3 | 230 VAC | 315 | 63 | No | 3U | 5.25 |

Each fan is rated for 22W - 0.57A at 115Vac.

Data subject to change without notice

© 2024. Hammond Manufacturing Ltd. All rights reserved.