


375W PowerVerter Ultra-Compact Car Inverter with 2 Outlets

MODEL NUMBER: PV375



Highlights

- 12V DC input; 120V AC output; 2 outlets
- 375 watts continuous output
- 600 watts peak output (instantaneous)
- Convenient cigarette lighter plug

Package Includes

- PV375 Inverter
- Warranty information
- Instruction manual

Description

Utilize your vehicle's battery to efficiently power office equipment on the road. Continuously supplies up to 375 watts of 120V AC power to 2 AC outlets from any 12V battery or automotive DC source. Convenient cigarette lighter DC input jack with 3-ft. (0.91 m) cable provides 1-step installation. Portable and compact, the inverter's design is among the most rugged available thanks to its lightweight metal casing.

Features

- Allows users to run AC devices from any 12V cigarette lighter socket
- Converts 12V DC battery power to 120V AC power
- 375 watts continuous output power; 600 watts peak output power (instantaneous)
- 2 outlets
- 3-ft. (0.91 m) cord with cigarette lighter plug
- Ultra compact, lightweight design with all-metal housing
- Low battery alarm with auto-shutoff preserves vehicle battery
- Overload alarm with auto-shutoff prevents wattage overload
- Replaceable 40amp fuse protects inverter from overload
- Lighted power switch

Specifications

| OVERVIEW | |
|----------------------------|---|
| UPC Code | 037332119841 |
| INPUT | |
| Maximum Input Amps / Watts | Full continuous load - 40A at 12V DC, No load - 0.65A at 12V DC |
| Input Connection Type | 12V DC cigarette lighter input plug connection |



Powering Business Worldwide



| | |
|--|---|
| Input Cord Length Details | 3 ft. hardwire input cable, 16 gauge, 2 wire |
| Voltage Compatibility (VDC) | 12 |
| OUTPUT | |
| Frequency Compatibility | 60 Hz |
| Pure Sine Wave Output | No |
| Nominal Output Voltage(s) Supported | 120V |
| Output Receptacles | (2) 5-15R |
| Continuous Output Capacity (Watts) | 375 |
| Peak Output Capacity (Watts) | 600 |
| Output Voltage Regulation | Maintains PWM sine wave output voltage of 115 V AC (+/- 8 VAC) |
| Output Frequency Regulation | 60 Hz (+/- 3 Hz) |
| Overload Protection | 40A automotive input fuse |
| BATTERY | |
| DC System Voltage (VDC) | 12 |
| USER INTERFACE, ALERTS & CONTROLS | |
| Switches | Lighted on/off power switch |
| Audible Alarm | Dual function alarm indicates overload conditions or low DC input voltage of 10.5V or less. |
| PHYSICAL | |
| Material of Construction | Aluminum, Steel |
| Cooling Method | Fan |
| Shipping Dimensions (hwd / in.) | 2.50 x 5.80 x 7.70 |
| Shipping Dimensions (hwd / cm) | 6.35 x 14.73 x 19.56 |
| Shipping Weight (lbs.) | 2.18 |
| Shipping Weight (kg) | 0.99 |
| Unit Dimensions (hwd / in.) | 2.000 x 4.250 x 7.000 |
| Unit Dimensions (hwd / cm) | 5.08 x 10.8 x 17.78 |
| Unit Weight (lbs.) | 2.3 |
| Unit Weight (kg) | 1.04 |
| ENVIRONMENTAL | |
| Relative Humidity | 0%-95% Non-Condensing |
| STANDARDS & COMPLIANCE | |
| Product Compliance | RoHS |



Powering Business Worldwide



| WARRANTY & SUPPORT | |
|-------------------------------------|-------------------------|
| Product Warranty Period (Worldwide) | 1-year limited warranty |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.