# 7-Port USB 2.0 Hub, Tower

MODEL NUMBER: **U222-007-R**












## Highlights

- Connect up to 7 USB 2.0 devices
- Hi-Speed 480Mbps data transfer
- Backward compatible with USB 1.1 devices
- Over-current protection safeguards connected equipment from overvoltages
- Supports USB 2.0 spec up to 500mA per port
- Includes base stand for upright positioning
- Compatible with all major operating systems

## System Requirements

- USB 2.0 port
- Compatible with all major operating systems

## Package Includes

- U222-007-R USB 2.0 7-Port Mini Hub
- Compact External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2.5A)
- 4 ft. extension cable

## Description

This 7-port USB 2.0 hub allows you to connect up to seven USB devices to a single USB port on your computer. This unit meets or exceeds USB 2.0 specifications for Hi-Speed data transmission rates up to 480 Mbps. Perfect for both the mobile and desktop user. While the hub will function perfectly in virtually all cases without needing external power, a compact, multi-voltage AC adapter (100-240V) has been provided for the rare circumstance when connecting a power-hungry device. This USB 2.0 device is backwards compatible so that it will function with both USB 2.0 and USB 1.1 devices. Over-current protection safeguards connected equipment from overvoltages. Includes stand for upright positioning.

## Features

- USB2.0 7-Port Hub
- Supports data transfer rates up to 480Mbps
- Connect up to 7 USB devices to a single USB port on your computer
- Compact design is ideal for use with a laptop/notebook computer
- Does not require external power, software, or complicated set-up procedures
- Plug-and-play/hot-swappable allows you to add or remove a device at any time
- Per-port overcurrent protection
- Bus-powered or self-powered
- Supports USB 2.0 spec up to 500mA per port
- On bus-power, 500mA from the USB 2.0 computer port is shared between the hub ports
- The included external power supply provides 2.5A of power, to be shared between the hub ports (up to 500mA per port)
- Compact, multi-voltage power supply (100-240V) provided
- Compatible with all major operating systems

# Specifications

| OVERVIEW | |
|---|---|
| UPC Code | 037332126733 |

| | |
|---|---|
| Product Type | Hub |
| Technology | USB 2.0 (High Speed) |
| Host Connector | USB A (MALE) |
| **VIDEO** | |
| Number of Monitors Supported | 0 |
| Extended Mode | No |
| Mirror Mode | No |
| **DATA** | |
| Data Ports | (7) USB A (FEMALE) |
| Data Ports Details | (7) USB-A - USB 2.0 |
| **INPUT** | |
| AC Power Adapter Plug(s) | NEMA 1-15P North America |
| AC Power Adapter Input Specs (V / Hz / A) | 100-240V / 50/60Hz / 0.5A |
| AC Power Adapter Output Specs (V / A) | 5V / 2.5A |
| AC Power Adapter Cord Length (ft.) | 5 |
| AC Power Adapter Cord Length (m) | 1.5 |
| Voltage Compatibility (VAC) | 100; 110; 120; 125; 127; 200; 208; 220; 230; 240 |
| Bus Powered | No |
| **POWER** | |
| Power Source Type | AC Adapter |
| AC Adapter | Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2.5A |
| DC Barrel Plug | OD: 3.5 x 1.35 x 9.5mm, Positive Pin, Negative Sleeve |
| **USER INTERFACE, ALERTS & CONTROLS** | |
| LED Indicators | Red - Power |
| **PHYSICAL** | |
| Color | Black; White |
| Material of Construction | Plastic |
| Shipping Dimensions (hwd / in.) | 8.90 x 5.60 x 2.50 |
| Shipping Weight (kg) | 0.45 |
| Unit Dimensions (hwd / in.) | 3.500 x 1.000 x 2.750 |
| Unit Packaging Type | Clamshell |

| | |
|---|---|
| Unit Weight (lbs.) | 0.2 |
| Unit Weight (kg) | 0.09 |
| **ENVIRONMENTAL** | |
| Operating Temperature Range | 32° to 104°F (0° to 40°C) |
| Storage Temperature Range | 14° to 176°F (-10° to 80°C) |
| Relative Humidity | 0% to 90 RH, Non-Condensing |
| BTUs | 8.5 BTU/Hr |
| **CONNECTIONS** | |
| Number of Ports | 7 |
| Side A - Connector 1 | USB B (FEMALE) |
| Side B - Connector 1 | (7) USB A (FEMALE) |
| Connector Plating | Nickel |
| **FEATURES & SPECIFICATIONS** | |
| Over Current Protection | Yes |
| USB Hub Ports | Yes |
| Number of USB Hub Ports | 7 |
| USB Specification | USB 2.0 (up to 480 Mbps) |
| Driver Required | No |
| **STANDARDS & COMPLIANCE** | |
| TAA Compliant Option | N |
| External Power Supply Certifications | FCC; UL; cUL; RoHS |
| Product Compliance | RoHS; CE (Europe); REACH; FCC (USA) |
| **WARRANTY & SUPPORT** | |
| Product Warranty Period (Worldwide) | 3-year limited warranty |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
https://tripplite.eaton.com

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.