CUI INC
a bel group

SERIES: VSK-S5 | DESCRIPTION: AC-DC POWER SUPPLY

DISCONTINUED

FEATURES

- up to 5.5 W continuous output
- compact board mount design
- universal input (85~264 Vac/110~370 Vdc)
- single regulated output from 3.3~24 Vdc
- over voltage, over temperature, and short circuit protections
- UL/cUL safety approvals
- efficiency up to 83%



MODEL

MODEL	output voltage (Vdc)	output current max (mA)	output power max (W)	ripple and noise[1] max (mVp-p)	efficiency max (%)
VSK-S5-3R3UA*	3.3	1250	4.125	120	74
VSK-S5-5UA*	5	1000	5	120	78
VSK-S5-9UA*	9	550	5	100	78
VSK-S5-12UA	12	420	5	100	80
VSK-S5-15UA*	15	333	5	100	82
VSK-S5-24UA*	24	230	5.5	100	83

Notes: 1. Ripple and noise are measured at 20 MHz BW by "parallel cable" method with 1 µF ceramic and 10 µF electrolytic capacitors on the output.
2. * Discontinued model.

PART NUMBER KEY

VSK-S5 - XXUA

Base Number — Output Voltage

INPUT

parameter	conditions/description	min	typ	max	units
voltage		85 110		264 370	Vac Vdc
frequency		47		63	Hz
current	at 110 Vac at 230 Vac		110 70		mA mA
inrush current	at 110 Vac at 230 Vac		10 20		A A
input fuse	recommended external 1 A/250 V, slow-blow type				
temperature coefficient			±0.02		%/°C

OUTPUT

parameter	conditions/description	min	typ	max	units
capcitive load[1]	3.3 Vdc model 5 Vdc model 9 Vdc model 12 Vdc model 15 Vdc model 24 Vdc model			4000 4000 1000 820 820 330	µF µF µF µF µF µF
line regulation			±0.5		%
load regulation	at 10~100% load		±1		%
voltage set accuracy	3.3 Vdc model all other models		±3 ±2		% %
hold-up time	at 110 Vac at 230 Vac		12 80		ms ms
switching frequency				140	kHz

Notes: 1. Test without external circuit

PROTECTIONS

parameter	conditions/description	min	typ	max	units
over voltage protection	shutdown				
over current protection	auto recovery	110			%
short circuit protection	hiccup, auto recovery				

SAFETY & COMPLIANCE

parameter	conditions/description	min	typ	max	units
isolation voltage	for 1 minute	4,000			Vac
safety approvals	UL60950-1				
safety class	Class II				
conducted emissions	CISPR22/EN55022, Class B				
radiated emissions	CISPR22/EN55022, Class B				
ESD	IEC/EN61000-4-2 Class B, contact ±6 kV / air ±8 kV				
radiated immunity	IEC/EN61000-4-3 Class A, 10V/m				
EFT/burst	IEC/EN61000-4-4 Class B, ±2 kV				
	IEC/EN61000-4-4 Class B, ±4 kV (external circuit required, see figure 2)				
surge	IEC/EN61000-4-5 Class B, ±1 kV / ±2 kV				
	IEC/EN61000-4-5 Class B, ±2 kV / ±4 kV (external circuit required, see figure 2)				
conducted immunity	IEC/EN61000-4-6 Class A, 10 Vr.m.s				
PFM	IEC/EN61000-4-8 Class A, 10 A/m				

DISCONTINUED


SAFETY & COMPLIANCE (CONTINUED)


parameter	conditions/description	min	typ	max	units
voltage dips & interruptions	IEC/EN61000-4-11 Class B, 0%-70%				
MTBF	as per MIL-HDBK-217F, at 25 °C	300,000			hours
RoHS	2011/65/EU				


ENVIRONMENTAL

parameter	conditions/description	min	typ	max	units
operating temperature	see derating curves	-25		70	°C
storage temperature		-25		105	°C
storage humidity	non-condensing			95	%


DERATING CURVES








EFFICIENCY CURVES





DISCONTINUED

MECHANICAL

parameter	conditions/description	min	typ	max	units
dimensions	50.8 x 25.4 x 15.16 (2.00 x 1.00 x 0.597 inch)				mm
material	UL94V-0				
weight			31		g

MECHANICAL DRAWING


units: mm [inch]
tolerance: ±0.50 [±0.020]
pin section tolerance: ±0.10 [±0.004]

PIN CONNECTIONS	
PIN	FUNCTION
1	AC(N)
2	AC(L)
3	+Vo
4	-Vo




Front View

Grid Size: 2.54 x 2.54mm



Top View

PCB LAYOUT



Bottom View

DISCONTINUED

TYPICAL APPLICATION CIRCUIT

Figure 1




Table 1

Recommended External Circuit Components					
MODEL	C1[1] (µF)	C2[1] (µF)	FUSE	NTC	MOV
VSK-S5-3R3UA	1	220	1 A/250 V	12D-5	S14K350
VSK-S5-5UA	1	220	1 A/250 V	12D-5	S14K350
VSK-S5-9UA	1	100	1 A/250 V	12D-5	S14K350
VSK-S5-12UA	1	100	1 A/250 V	12D-5	S14K350
VSK-S5-15UA	1	100	1 A/250 V	12D-5	S14K350
VSK-S5-24UA	1	47	1 A/250 V	12D-5	S14K350

Note: 1. Output filtering capacitor C1 is a ceramic capacitor that is used to filter high frequency noise. C2 is an electrolytic capacitor. It is recommended to use high frequency and low impedance electrolytic capacitors. For capacitance and current of capacitor please refer to the manufacturer's datasheet. Voltage derating of capacitor should be 80% or above.

EMC RECOMMENDED CIRCUIT

Figure 2




Table 2

Recommended External Circuit Components	
FUSE	1A/250V, slow fusing, necessary
MOV	S14K350
CY1, CY2	1nF/400VAC
CX	0.1µF/275VAC
LCM	2.2mH
L1	4.7µH/2.0A
C1, C2	see Table 1

DISCONTINUED

Note: 1. All specifications measured at Ta=25°C, humidity <75%, nominal input voltage, and rated output load, unless otherwise specified.

REVISION HISTORY

rev.	description	date
1.0	initial release	07/26/2011
1.01	new template applied	03/06/2012
1.02	V-Infinity branding removed	08/21/2012
1.03	added efficiency curves	12/10/2012
1.04	updated spec	04/01/2013
1.05	updated spec	08/23/2013
1.06	updated spec	01/08/2014
1.07	changed internal IC, updated datasheet	06/05/2015
1.08	company logo updated	10/30/2020
1.09	UKCA mark added, derating and efficiency curves and circuit figures updated	06/01/2022
1.10	discontinued models VSK-S5-15UA, VSK-S5-24UA, VSK-S5-9UA, VSK-S5-3R3UA	11/11/2022
1.11	discontinued model VSK-S5-5UA	12/14/2022

The revision history provided is for informational purposes only and is believed to be accurate.

DISCONTINUED

CUI INC
a bel group

Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.